

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)


PCT

(10) International Publication Number
WO 2005/003003 A1

- (51) International Patent Classification⁷: **B65G 47/76**, 47/84 // B07C 3/06
- (21) International Application Number: PCT/NO2004/000167
- (22) International Filing Date: 10 June 2004 (10.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 20033014 1 July 2003 (01.07.2003) NO
- (71) Applicant (for all designated States except US): **TOMRA SYSTEMS ASA** [NO/NO]; Drengsrudhagen 2, N-1385 Asker (NO).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LARGE, Bengt** [NO/NO]; Tennisveien 23B, N-0777 Oslo (NO). **ONSTAD, Hans, Georg** [NO/NO]; Ribberkleiva 50E, N-1386 Asker (NO).
- (74) Agent: **LANGFELDT, Jens, F., C.**; Zacco Norway AS, P.O. Box 765, Sentrum, N-0106 Oslo (NO).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: SORTER DEVICE



(57) Abstract: A device for directionally guiding articles of different shapes that are being conveyed on a conveyor off the conveyor with the aid of a movable gate (8-11) that is controllable (23-25) to move across the conveyor (1) at an angle to the direction of travel of the article on the conveyor. The gate is made having a means (8) which, upon movement across the conveyor, is designed to forcibly cause the article to be driven along the gate, in a direction corresponding to said angle, off the conveyor (1) and to an exit (6, 6'; 6'', 6'''). Advantageously, the means consists of at least one motor-driven, rotatable disc.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.